

|   |                            |
|---|----------------------------|
| Dimension (L*W*H)                         | 1970×1230/1430/1630x2380mm |
| Weight (With Battery)                     | 1250kg                     |
| Load                                      | 2T                         |
| Lift                                      | 37cm                       |
| Turning Radius                            | 1530mm                     |
| Fork Dimension (L*W*H)                    | 1070*134*40mm              |
| Charging Mode                             | Manual/Automatic           |
| Time to Full Charge                       | <2h                        |
| Continuous Working Time after Full Charge | 5-8h                       |

|  |                                   |
|--|-----------------------------------|
| Voltage and Capacity                           | 48V / 202Ah                       |
| Maximum Travel Speed (Loaded / Unloaded)       | 7.2 / 9 km/h                      |
| Walking Precision                              | ±30 mm (Outdoor) / ±20 mm(Indoor) |
| Stopping Precision                             | ±30 mm (Outdoor) / ±10 mm(Indoor) |
| Maximum Climbable Gradient (Loaded / Unloaded) | 10% / 15%                         |
| Navigation System                              | LSLiDAR 3D SLAM                   |
| Navigation Mode                                | Natural Navigation                |
| Communication Mode                             | Supports 5G                       |
| Moving Function                                | Forward/ Backward/Turn            |